

## COMPOUND MITER SAW SAFETY RULES

1. THE SAFETY ZONE WHERE YOUR FINGERS SHOULD NOT BE WHEN CUTTING IS 6 INCHES ON EITHER SIDE OF THE BLADE.
2. THE LOCK DOWN PIN SECURES THE SAW IN THE LOWER POSITION.
3. THE MITER CLAMP KNOB LOCKS THE SAW AT THE DESIRED ANGLE.
4. THE SAFETY GUARD COVERS THE SAW BLADE IN THE RAISED AND LOWERED POSITIONS.
5. TIGHTEN THE BEVEL CLAMP KNOB TO SET THE BEVEL ANGLE AT THE DESIRED ANGLE CUT.
6. THE SPINDLE LOCK BUTTON HOLDS THE BLADE WHILE CHANGING.
7. DO NOT STAND IN LINE WITH THE SAW BLADE WHEN CUTTING.
8. THE TEETH OF THE SAW BLADE SHOULD POINT BACK TOWARDS THE FENCE.
9. WHEN FINISHED CUTTING A BOARD, LET THE SAW COAST TO A STOP BEFORE RAISING THE BLADE OUT OF THE WOOD.
10. A BEVEL AND A MITER CUT MADE AT THE SAME TIME PRODUCE A COMPOUND MITER CUT.
11. THE SAW BLADE DIAMETER IS 12"
12. THE LEFT FENCE NEEDS TO BE ADJUSTED OUT BEFORE MAKING A BEVEL CUT.